



DEO SAE 15W-40 Ultra

Keep everything running smoothly.

Description

DEO SAE 15W-40 Ultra is a high performance multi grade oil, which provides excellent lubrication. This Diesel Engine Oil is approved within **mtu** oil category 2 and ensures outstanding protection for your **mtu** engines.

Benefits

- High engine cleanliness and sludge control
- Good wear protection even under high stress
- Less corrosion independent of fuel composition
- Reliable operation in different climatic conditions

Classifications

- ACEA E7
- API CI-4/SL
- GLOBAL DHD-1
- ZF TE-ML 04C



Typical Characteristics

Density at 15 °C	DIN 51757	0,879 g/ml
Flash Point	DIN ISO 2592	232 °C
Pour Point	DIN ISO 3016	-33 °C
Kinematic Viscosity at 40 °C	DIN 51562-1	114.9 mm ² /s
Kinematic Viscosity at 100 °C	DIN 51562-1	14,9 mm ² /s
Viscosity index	DIN ISO 2909	135
Sulfate ash	ASTM D874	≤2.0 % m/m
Change intervals	w/o oil centrifuge: 500 operating hours w oil centrifuge or by-pass oil filter: 1000 operating hours	
Storage stability	Shelf life of at least three years when stored in unopened, original containers between 5 and 40°C. Containers must not be exposed solar radiation, freezing temperatures or rain.	

DEO SAE 15W-40 Ultra is approved for the following engine series:

- S60 (min. API CH-4)
- Series 99, 183, 396, 538, 595 (w / w/o carbon scraper ring)
- Series 956*, 956-01/-02 Marine/Rail
- Series 1163-02/-03/-04 Marine
- Series 2000Mx3/ Mx4 / 2000M72
- Series 2000Cx6 / Gx5/ Gx6 / Gx7 / Mx6 / Sx6
- Series 2000CxO/Cx1/Cx2
- Series 2000Mx0/Mx1 (not 2000M41A IMO III)
- Series 2000 Px2/Sx0/Sx1/Sx2
- Series 4000-00/-01/-02
- Series 4000/03G/S/P/C/R
4000-03Gx3F / Gx3G / Gx3H
- Series 4000M23F - M63L**
- Series 4000M53/M73-M93L/N43/N83**
- Series 4000-03M73-M93L IMO II SCR ready
- Series 4000-03R63x
- Series 12V4000U83
- Series 4000-04 B / G / M
- Series 4000-05 M** / 4000-05 M IMO II
- 6R, 10V, 12V 1600:
Gendrive: G10F – G80S
- 12V 1600:
Gendrive: G11F – G91S
- 10V, 12V 1600:
C&I: C50, C60, C70
Agriculture: A50, A60, A70
O&G: T50, T60, T70
- 6R 1600 M Marine
- Diesel Engine-Generator Sets: 2000Gx5, 2000Gx6, 4000Gx3, 4000Gx4

*Excl. NPP standby power

**Not approved for operation with SCR-systems (Selective Catalytic Reduction)

Health / Safety

Based on available information, this product is not expected to have adverse health effects when it is used for the intended application and the recommendations provided in the Material Safety Data sheet (MSDS) are followed. MSDSs are available upon request through your sales contact. If disposing the used product, take care to protect the environment.

Part No.	Designation	Container
X00084315	DEO SAE 15W-40 Ultra	20 Liters
X00084316	DEO SAE 15W-40 Ultra	210 Liters

The respective Fluids and Lubricants Specifications apply first and foremost.

Subject to change without notice 07/2024 - valid for Europe | Middle East | Africa